

<b>Hardware Features</b>	<b>Model</b>	<b>Reolink Argus® 2</b>	
	Image Sensor	Starlight CMOS Image Sensor	
	Display Resolution	1920 x 1080 (2.0 Megapixel)	
	Lens	F = 3.26 mm Fixed, F = 2.2, With IRCUT	
	Angle of View	Diagonal: 130° (Horizontal: 105°, Vertical: 55°)	
	PIR Detecting Distance	Low: 2-4 Meters, Mid: 4-6 Meters, High: 6-9 Meters	
	PIR Detecting Angle	Horizontal: 120°	
	Minimum Illumination	0 Lux (With IR Illuminator)	
	IR Distance	Up to 10 Meters	
	Dimensions	96 x 58 x 59 mm	
	Weight(battery included)	260 g	
	Interface		Built-in Micro SD socket
			Built-in Microphone and Speaker
			Micro USB Battery Charge Interface
		Reset Button	
<b>Software Features</b>	Protocols & Standards	SSL, TCP/IP, UDP, SMTP, DHCP, DNS, P2P	
	Image Compression	H.264	
	Maximal Frame Rate	15 fps	
	Code rate	768 Kbps ~ 2048 Kbps	
	Audio	Two-way Audio	
	Browser Supported	Not Available	
	OS Supported	Smartphone: iOS, Android Computer: Windows, Mac	
	Standby Awaken	PIR Alarm, Remote Access, Reset Button	
	Record Mode	PIR Alarm Record	
<b>WiFi</b>	Wireless Standard	IEEE 802.11 b/g/n	
	Operating Frequency	2.4 GHz	
	Wireless Security	WEP/WPA-PSK/WPA2-PSK	
<b>Battery</b>	Type Specification	18650 Rechargeable Lithium Battery 5200 mAh/3.63 V, Supports Solar Power	
	Battery Level Indication	Yes	
	Ordinary Life	4 - 6 Months	
<b>Other Parameters</b>	Temperature	Operating Temperature : -10°C ~ +55 °C	
	Humidity	Operating Humidity: 20% ~ 85%	
	Waterproof Level	Weatherproof: IP65	